



# CLIMB FASTER. WORK SAFER.

PowerPole makes traditional scaffolding and pump jack systems a thing of the past. The streamlined design grants you quick access up to 78 ft. Remove the manual labor of pumping or cranking and replace it with easy, powered access!

## FAST + EFFICIENT

- Quick setup with no roof rigging
- Perfect for tight spaces
- Accommodates platforms up to 28 in. wide
- Landscape-friendly setup
- Three times faster than a pump jack

## IDEAL FOR:

- Siding, painting, and wall coating
- Window installation, caulking, and glazing
- Tuckpointing, patching, and repair
- Waterproofing and cleaning



### ACCESS EQUIPMENT COMPARISON (WORKING HEIGHTS UP TO 78 FT)

Access Equipment	PowerPole	Swing Stage	Boom/Scissor	Mast Climber	Scaffolding
Setup Cost	Best	Good	Better	Fair	Fair
Portability	Best	Good	Fair	Fair	Fair
Tight Spots	Best	Good	Fair	Fair	Fair
Work at Ideal Height	Best	Better	Better	Better	Poor
Landscape-Friendly Design	Best	Good	Fair	Fair	Fair

## » POWERPOLE SPECIFICATIONS

GENERAL SPECIFICATIONS	
Maximum Rated Load on Climbing Unit	650 lbs (1,300 lbs per pair)
Safety Devices	Lock Lever, Manual Crank, Integrated Overspeed Brake
Maximum Climbing Speed at 1/2 Rated Load	25 ft/min
Maximum Climbing Speed at Rated Load	15 ft/min
Maximum Lowering Speed	30 ft/min
Maximum Platform Height	72 ft
Maximum Work Height	78 ft
Platform Sizes	Up to 40 ft x 28 in.
Basket Size	26 in. x 36 in. x 42 in.

POWERPOLE TILT-UP SPECIFICATIONS	
Maximum Midspan Tie Spacing	16 ft
Maximum Untied Work Height (Requires Outriggers)	24 ft
Maximum Height without Midspan Tie (with Outriggers)	40 ft

**Note:** These specifications are taken from the Operators Manual and are subject to change. Refer to the Operators Manual for detailed specifications and information on proper usage and maintenance.

## » SYSTEM FEATURES

### CLIMBING UNIT + GEARBOX

Powered by a 1/2 in. drill, the 650 lb load rated PowerTrak system provides 3x the speed of a pump jack system. Our durable gearbox eliminates typical electrical components, keeps the system lightweight, and features an overspeed brake for added safety.



### QUICK ATTACH POLES + COUPLERS

Updated, streamlined, extruded aluminum poles are lightweight for easy hauling and installation. The tools-free coupler allows for quick assembly. The pole's contoured profile assists with grip, both during assembly and when tilting the system into place.



## SYSTEM ACCESSORIES


### OUTRIGGER ASSEMBLY

The rugged steel stabilizers keep you pressed into the wall, allowing a 24 ft work height without tying into the structure. Each side of the outrigger has a stabilizer that adjusts 8 in. to level the system.



### SINGLE + DUAL SIDED POWERLATCH ASSEMBLY

Choose the single-sided PowerLatch for most applications, or the dual-sided to connect a platform support on each side of the climbing unit or to use our single man basket.



### EXTENDABLE V-BRACE

The extendable v-brace, when retracted, is the same size as the standard v-brace, and can move in 2 in. increments to expand for a total wall distance of 51 in.



### SUPER STANDOFF TIE

The super standoff tie has extra long tubes to allow roof access. By placing the platform at roof level, the PowerPole tilt-up system can serve as roofline fall protection.



### SINGLE BASKET

The basket features dual entry and a large 36 in. wide by 26 in. deep work area, providing ample working space for you and your tools. The basket quickly attaches to the climbing unit via the PowerLatch interface.

