



CLIMB FASTER. WORK SAFER.

PowerPole makes traditional scaffolding and pump jack systems a thing of the past. The streamlined design grants you quick access up to 75 feet. Remove the manual labor of pumping or cranking and replace it with easy, powered access!

FAST + EFFICIENT

- Quick setup with no roof rigging
- Perfect for tight spaces
- Accommodates platforms up to 28 in. wide
- Landscape-friendly setup
- Three times faster than a pump jack

IDEAL FOR:

- Siding, painting, and wall coating
- Window installation, caulking, and glazing
- Tuckpointing, patching, and repair
- Waterproofing and cleaning



ACCESS EQUIPMENT COMPARISON (WORKING HEIGHTS UP TO 75 FT)

| Access Equipment | PowerPole | Swing Stage | Boom/Scissor | Mast Climber | Scaffolding |
|---------------------------|-----------|-------------|--------------|--------------|-------------|
| Setup Cost | Best | Good | Better | Fair | Fair |
| Portability | Best | Good | Fair | Fair | Fair |
| Tight Spots | Best | Good | Fair | Fair | Fair |
| Work at Ideal Height | Best | Better | Better | Better | Poor |
| Landscape-Friendly Design | Best | Good | Fair | Fair | Fair |

» POWERPOLE SPECIFICATIONS

| GENERAL SPECIFICATIONS | |
|--|--|
| Maximum Rated Load on Climbing Unit | 650 lbs (1,300 lbs per pair) |
| Safety Devices | Lock Lever, Manual Crank, Integrated Overspeed Brake |
| Maximum Climbing Speed at 1/2 Rated Load | 25 ft/min |
| Maximum Climbing Speed at Rated Load | 15 ft/min |
| Maximum Lowering Speed | 30 ft/min |
| Maximum Platform Height | 69 ft |
| Maximum Work Height | 75 ft |
| Platform Sizes | Up to 40 ft x 28 in. |
| Basket Size | 26 in. x 36 in. x 42 in. |

| POWERPOLE TILT-UP SPECIFICATIONS | |
|--|-------|
| Maximum Midspan Tie Spacing | 16 ft |
| Maximum Untied Work Height (Requires Outriggers) | 24 ft |
| Maximum Height without Midspan Tie (with Outriggers) | 40 ft |

Note: These specifications are taken from the Operators Manual and are subject to change. Refer to the Operators Manual for detailed specifications and information on proper usage and maintenance.

» SYSTEM FEATURES

CLIMBING UNIT + GEARBOX ▾

Powered by a 1/2 in. drill, the 650 lb load rated PowerTrak system provides 3x the speed of a pump jack system. Our durable gearbox eliminates typical electrical components, keeps the system lightweight, and features an overspeed brake for added safety.



QUICK ATTACH POLES + COUPLERS ▾

Updated, streamlined, extruded aluminum poles are lightweight for easy hauling and installation. The tools-free coupler allows for quick assembly. The pole's contoured profile assists with grip, both during assembly and when tilting the system into place.



SYSTEM ACCESSORIES


OUTRIGGER ASSEMBLY ▾

The rugged steel stabilizers keep you pressed into the wall, allowing a 24 feet work height without tying into the structure. Each side of the outrigger has a stabilizer that adjusts 8 inches to level the system.



SINGLE + DUAL SIDED POWERLATCH ASSEMBLY ▾

Choose the single-sided PowerLatch for most applications, or the dual-sided to connect a platform support on each side of the climbing unit or to use our single man basket.



EXTENDABLE V-BRACE ▾

The extendable v-brace, when retracted, is the same size as the standard v-brace, and can move in 2 inch increments to expand for a total wall distance of 51 inches.



SUPER STANDOFF TIE ▾

The super standoff tie has extra long tubes to allow roof access. By placing the platform at roof level, the PowerPole tilt-up system can serve as roofline fall protection.



SINGLE BASKET ▾

The basket features dual entry and a large 36 inch wide by 26 inch deep work area, providing ample space for you and your tools. The basket quickly attaches to the climbing unit via the PowerLatch interface.

